


1900 M

MAXIBLOCK CABLE GLAND, IN POLYAMIDE PA6.6, METRIC PITCH, IP68



CERTIFICATIONS & APPROVALS



Features

TECHNICAL INFORMATION

Range of operating temperature (dynamic)	-20 ÷ 90 °C
Range of operating temperature (static)	-40 ÷ 100 °C
Ingress Protection	IP68
Counter nut	No
Dust-proof disc	No
Internal washers	No
EMC	No
Markings found	factory mark; thread type; certification logos
Reference standard	CEI EN 60423; CEI EN 62444
Self-extinguishing fire class according to UL 94	V2

MATERIAL COMPOSITION AND TREATMENTS


Entry bush material	Poliammide PA6.6
Inner seal material	Neoprene
Body material	Poliammide PA6.6
Halogen free	No

LOGISTIC

Type of packaging	; box
Customs code	39269097

CLASSIFICATION AND DATA ORDERING

ETIM Class 7	Cable gland [EC000441]
--------------	------------------------



1900 M

tipo	P	External seal	Colour	Outer seal material	Tightening torque [nm]	Range of cable housing diameter [mm]	B1 [mm]	B2 [mm]	C [mm]	L [mm]	Fixing hole diameter [mm]	Width [mm]	Gross weight [g]	Unit in standard packaging [pce]	Minimum order quantity [pce]
1900.M12	M12x1,5	No	Grey RAL 7035		2.7	3.5 ÷ 7	15	15	8	18 ÷ 22	12.2	16.5	3,460	100	100
1900.M12N	M12x1,5	No	Black RAL 9005		2.7	3.5 ÷ 7	15	15	8	18 ÷ 22	12.2	16.5	3,520	100	100
1900.M12G	M12x1,5	No	Dark grey RAL 7001		2.7	3.5 ÷ 7	15	15	8	18 ÷ 22	12.2	16.5	3,480	100	100
1900.M16	M16x1,5	No	Grey RAL 7035		5	5 ÷ 10	19	19	8	22 ÷ 27	16.2	21.4	6,620	100	100
1900.M16N	M16x1,5	No	Black RAL 9005		5	5 ÷ 10	19	19	8	22 ÷ 27	16.2	21.4	6,580	100	100
1900.M16G	M16x1,5	No	Dark grey RAL 7001		5	5 ÷ 10	19	19	8	22 ÷ 27	16.2	21.4	6,520	100	100
1900.M20	M20x1,5	No	Grey RAL 7035		7	7 ÷ 13	25	25	9	24 ÷ 30	20.5	25	11,280	100	100
1900.M20N	M20x1,5	No	Black RAL 9005		7	7 ÷ 13	25	25	9	24 ÷ 30	20.5	25	11,060	100	100
1900.M20G	M20x1,5	No	Dark grey RAL 7001		7	7 ÷ 13	25	25	9	24 ÷ 30	20.5	25	11,220	100	100
1900.M25	M25x1,5	No	Grey RAL 7035		7.5	10 ÷ 17	30	30	10	28 ÷ 39	25.4	33	18,560	50	50
1900.M25N	M25x1,5	No	Black RAL 9005		7.5	10 ÷ 17	30	30	10	28 ÷ 39	25.4	33	18,120	50	50
1900.M25G	M25x1,5	No	Dark grey RAL 7001		7.5	10 ÷ 17	30	30	10	28 ÷ 39	25.4	33	18,200	50	50
1900.M32	M32x1,5	Yes	Grey RAL 7035	Neoprene	8	13 ÷ 21	36	36	10	33 ÷ 44	32.5	39.5	29,200	25	25
1900.M32N	M32x1,5	Yes	Black RAL 9005	Neoprene	8	13 ÷ 21	36	36	10	33 ÷ 44	32.5	39.5	28,480	25	25
1900.M32G	M32x1,5	Yes	Dark grey RAL 7001	Neoprene	8	13 ÷ 21	36	36	10	33 ÷ 44	32.5	39.5	28,000	25	25
1900.M40	M40x1,5	Yes	Grey RAL 7035	Neoprene	8	19 ÷ 28	46	46	10	36 ÷ 45	40.5	51	49,867	15	15
1900.M40N	M40x1,5	Yes	Black RAL 9005	Neoprene	8	19 ÷ 28	46	46	10	36 ÷ 45	40.5	51	52,500	15	15

tipo	P	External seal	Colour	Outer seal material	Tightening torque [nm]	Range of cable housing diameter [mm]	B1 [mm]	B2 [mm]	C [mm]	L [mm]	Fixing hole diameter [mm]	Width [mm]	Gross weight [g]	Unit in standard packaging [pce]	Minimum order quantity [pce]
1900.M40G	M40x1,5	Yes	Dark grey RAL 7001	Neoprene	8	19 ÷ 28	46	46	10	36 ÷ 45	40.5	51	50,000	15	15
1900.M50	M50x1,5	Yes	Grey RAL 7035	Neoprene	15	27 ÷ 35	55	55	12	43 ÷ 52	50.5	61	80,000	10	10
1900.M50N	M50x1,5	Yes	Black RAL 9005	Neoprene	15	27 ÷ 35	55	55	12	43 ÷ 52	50.5	61	80,800	10	10
1900.M50G	M50x1,5	Yes	Dark grey RAL 7001	Neoprene	15	27 ÷ 35	55	55	12	43 ÷ 52	50.5	61	80,000	10	10
1900.M63	M63x1,5	Yes	Grey RAL 7035	Neoprene	15	34 ÷ 45	66	66	12	45 ÷ 55	64	72	117,780	5	5
1900.M63N	M63x1,5	Yes	Black RAL 9005	Neoprene	15	34 ÷ 45	66	66	12	45 ÷ 55	64	72	112,000	5	5
1900.M63G	M63x1,5	Yes	Dark grey RAL 7001	Neoprene	15	34 ÷ 45	66	66	12	45 ÷ 55	64	72	110,800	5	5