

2002

CABLE GLAND, IN NICKEL-PLATED BRASS, WITH RUBBER SEAL NR 55 sh A, PG PITCH, IP54



CERTIFICATIONS & APPROVALS



Features

TECHNICAL INFORMATION

Range of operating temperature (dynamic)	-25 ÷ 100 °C
Ingress Protection	IP54
External seal	No
Counter nut	No
Dust-proof disc	No
Internal washers	Yes
EMC	No
Colour	silver
Reference standard	DIN 40430; DIN 46320
Surface treatment	nichelatura

LOGISTIC


Type of packaging	; box
Customs code	74198090

MATERIAL COMPOSITION AND TREATMENTS

Entry bush material	ottone
Inner seal material	gomma NR 55 sh A
Body material	ottone
Minimum thickness surface coating	3 µm
Halogen free	No

CLASSIFICATION AND DATA ORDERING

ETIM Class 7	Cable gland [EC000441]
--------------	------------------------



2002

tipo	P	Range of cable housing diameter [mm]	B1 [mm]	B2 [mm]	C [mm]	L [mm]	Fixing hole diameter [mm]	Width [mm]	Gross weight [g]	Unit in minimal packaging [pce]	Unit in standard packaging [pce]	Minimum order quantity [pce]
200200721N	Pg7	5 ÷ 7	13	14	5	13 ÷ 16	12.7	14	8,345	100	400	100
200200921N	Pg9	8 ÷ 10	15	17	6	14 ÷ 17	15.5	17	12,203	100	300	100
200201121N	Pg11	8 ÷ 10	18	20	6	14 ÷ 18	18.8	20	18,100	50	200	50
200201321N	Pg13,5	10 ÷ 12	20	22	6.5	16 ÷ 19	20.5	22	22,160	50	100	50
200201621N	Pg16	12 ÷ 14	22	24	6.5	17 ÷ 20	22.6	24	27,520		50	50
200202121N	Pg21	17 ÷ 19	28	30	7	19 ÷ 23	28.5	30	44,840		50	50
200202921N	Pg29	26 ÷ 28	37	40	8	21 ÷ 25	37.2	40	75,200		15	15
200203621N	Pg36	33 ÷ 35	47	50	9	24 ÷ 30	47.2	50	126,600		10	10
200204221N	Pg42	39 ÷ 41	54	57	10	28 ÷ 34	54.2	57			10	10
200204821N	Pg48	43 ÷ 45	60	64	10	36 ÷ 45	60	64			10	10