


MG-TDM



Features

TECHNICAL INFORMATION

Minimum operating temperature	-40 °C
Maximum operating temperature	130 °C
Self-extinguishing fire class according to UL 94	V0

WEIGHT AND DIMENSIONS

Width	4 mm
Height of the printable area	4 mm

CLASSIFICATION AND DATA ORDERING

ETIM Class 7	Labelling material [EC001288]
---------------------	-------------------------------

MATERIAL COMPOSITION AND TREATMENTS

Material	Polycarbonate
Silicone-free	Yes
Halogen free	Yes

LOGISTIC

Storage temperature	10 ÷ 25 °C
Relative humidity of storage	45 ÷ 55
Customs code	39269097

COMPATIBILITY

Ribbon	MG2-ETR
Printable with	MG3; MG4
Plates	MG2-PTM

MG-TDM-01Range of cable housing diameter
1.6 ÷ 3.25 mmRange of cable cross section
0.5 ÷ 1.5 mm²

tipo	Colour	Sheet elements	Number of lines	Number of columns	L [mm]	Base of the printable area [mm]	Gross weight [g]	Software code
40190	White	66	6	11	12	12	0,273	121
40191	White	40	4	10	16	16	0,335	123
40192	White	40	4	10	12	12	0,335	119
40142	Yellow	40	4	10	12	12	0,336	119
40140	Yellow	66	6	11	12	12	0,276	121
40141	Yellow	40	4	10	16	16	0,338	123

MG-TDM-02Range of cable housing diameter
2 ÷ 4.4 mmRange of cable cross section
1 ÷ 6 mm²

tipo	Colour	Sheet elements	Number of lines	Number of columns	L [mm]	Base of the printable area [mm]	Gross weight [g]	Software code
40290	White	66	6	11	12	12	0,301	122
40291	White	40	4	10	16	16	0,363	124
40292	White	40	4	10	12	12	0,366	120
40242	Yellow	40	4	10	12	12	0,369	120
40240	Yellow	66	6	11	12	12	0,314	122
40241	Yellow	40	4	10	16	16	0,375	124